



## Digital Automatic Water meters Accuracy control where it counts



- Construction:** Basic meter equipped with non-corrosive bronze parts and built to our specifications by the world's largest manufacturer of water meters.
- Sanitation:** All working parts—meter, thermometer, and operating mechanism—fully exposed for ease of cleaning and to meet sanitation requirements. No hidden, hard-to-clean areas.
- Features:** Positive displacement—for exact measurement. Only one working part in measuring chamber for long life, simplicity of operation, and sustained accuracy.
- All rustless construction—non-corrosive bronze parts with composition rubber disk and ball.
- Built-in thermometer.
- Equipped for single faucet draw-off—one outlet independent of meter, for temperature stabilization.
- Mixing Valve:** Completely automatic thermostatic mixing valve controls delivered water temperature to within plus or minus 1/2 °F despite normal temperature and pressure changes in city or chilled water lines.
- Filter:** Valve equipped with bronze strainers which eliminate scale and other sediment. Easily removed for cleaning.
- Capacity:** Weighs up to 9,999 pounds—dial numbered to individual pounds. Meter available to measure kilograms, liters, gallons, if desired.
- Connection Requirements:** Independent water line from source and 110 volt electrical outlet (60 watts).
- Finish:** Completely assembled, ready for connections and wall mounting. Natural unpainted finish.
- Size:** Overall, including inlet and outlet, 24" wide x 12" high x 10" deep. Provided with two mounting bolt holes for easy mounting. Overall width with blending valve, 35".
- Weight:** Shipping weight: 85 pounds.

Model	Maximum Capacity	Voltage	Water Connection	Meter Dimension LxDxH
D-150	150 Lbs./Min.	1 ph 110V	1"	20"x8"x9"
D-300	300 Lbs./Min.	1 ph 110V	1 1/4"	24"x10"x12"

Standard Meters handle up to 120°F ingredient water.  
Hi-temp units available for up to 250°F if needed.

Larger Meters Available



CMC AMERICA CORPORATION • 208 S. CENTER ST. • JOLIET, ILLINOIS  
PHONE NUMBER (815) 726-4337 FAX (815) 726-7138

[www.doughmixer.com](http://www.doughmixer.com)